



### DIMENSIONS

FLANGE SIZE	2"	3"	4"	6"	8"	10"	12"	14"	16"
FLANGE O.D.	6 1/2"	8"	9 1/2"	11 1/2"	14"	16 1/2"	19 1/2"	21 1/2"	24"
CONNECTOR LENGTH	12"	14"	11 3/4"	14 1/8"	15 3/8"	17 3/4"	18 3/8"	20"	20"
BOLT DIAMETER	5/8"	5/8"	5/8"	3/4"	3/4"	7/8"	7/8"	1"	1"
BOLT LENGTH	2 1/2"	3"	3"	3 1/2"	4"	4"	4"	4"	4 3/4"
BOLT QUANTITY	4	4	8	8	8	12	12	12	16
SLEEVE DIAMETER	8"	10"	10"	12"	15"	18"	24"	24"	30"

- NOTES:
- THE PIPE SLEEVE IS MEANT TO RELIEVE PRESSURE ON THE SS BRAIDED FLEX CONNECTOR CREATED BY THE DOWNWARD FORCE OF THE BACKFILL.
  - PIPE SLEEVE SHALL BE BEDDED AND BACKFILLED PER FTS IMOG.
  - FIBERGLASS TANK SOLUTIONS TO SUPPLY GASKETS, HARDWARE, AND SLEEVE WITH SS BRAIDED FLEX CONNECTORS.
  - PIPE SLEEVE MUST EXTEND PAST THE FLANGES.

SHEET TITLE:  
**SS BRAIDED FLEX CONNECTOR INSTALLATION**

DRAWN DATE: 11/15/23	DRAWN BY: JACK	REV. 01
-------------------------	-------------------	------------

**Fiberglass Tank SOLUTIONS**

Mailing: P.O. BOX 326, Montreal, MO 65591  
 MFG: 147 Opportunity Rd.,  
 Camdenton, MO 65020  
 P: 573-317-9620