

ITEM	QTY	EQUIPMENT LISTING	
А	1	DRY INTERSTITIAL MONITOR HOUSING WITH 4" NPT FITTING	
В	1	WET INTERSTITIAL MONITORING RESERVOIR WITH 4" NPT FRP FITTING (OPTIONAL)	
С	3	4" NPT FULL COUPLING FRP SHELL WALL FITTING WITH STRIKER PLATE (OPTIONAL, 6" ALSO AVAILABLE)	
D	1	22" DIAMETER FRP MANWAY WITH STEEL COVER, 4-4" NPT HALF COUPLING STEEL FITTINGS IN COVER WITH STRIKER PLATE (OPTIONAL, 24" AND 30" DIAMETER COVERS ALSO AVAILABLE, UP TO 5 FITTINGS IN COVER, 2" AND 6" ALSO AVAILABLE, FULL COUPLINGS ALSO AVAILABLE)	
Е	1	42" DIAMETER X 6" TALL CONTAINMENT COLLAR (OPTIONAL, 48" DIAMETER ALSO AVAILABLE)	
F	2	FTS SUPPLIED LIFTING SLINGS (LIFTING LUGS ARE ONLY ADDED IF ORDERED AS AN OPTION - 6 LIFTING LUGS REQUIRED AS OPTION)	
G	8	18" WIDE X 8.75" TALL FTS-MANUFACTURED PREFABRICATED CONCRETE DEADMAN (2,400 LBS EA) + HOLD-DOWN STRAPS AND TURNBUCKLES	
><	12	FTS-SUPPLIED HOLD DOWN STRAP LOCATION	

	DOUBLE-WALL			
Fiberglass Tank	10-FT DIAMETER			
SOLUTIONS	40,000-GALLON TANK			
www.fgtsolutions.com	UL1316 - LISTED FUEL TANK			
TANK WEIGHT DRY-MONITORED	15,900 LBS			
TANK WEIGHT BRINE-MONITORED	18,000 LBS			
ACTUAL CAPACITY 40,126 GALLONS	DRAWING NUMBER: FTSP- 260-019 DATE: 09/22/25			