

QTY	EQUIPMENT LISTING
1	DRY INTERSTITIAL MONITOR HOUSING WITH 4" NPT FITTING
1	WET INTERSTITIAL MONITORING RESERVOIR WITH 4" NPT FRP FITTING (OPTIONAL)
3	4" NPT FULL COUPLING FRP SHELL WALL FITTING WITH STRIKER PLATE (OPTIONAL, 6" ALSO AVAILABLE)
1	22" DIAMETER FRP MANWAY WITH STEEL COVER, 4-4" NPT HALF COUPLING STEEL FITTINGS IN COVER WITH STRIKER PLATE (OPTIONAL, 24" AND 30" DIAMETER COVERS ALSO AVAILABLE, UP TO 5 FITTINGS IN COVER, 2" AND 6" ALSO AVAILABLE, FULL COUPLINGS ALSO AVAILABLE)
1	42" DIAMETER X 6" TALL CONTAINMENT COLLAR (OPTIONAL, 48" DIAMETER ALSO AVAILABLE)
2	FTS SUPPLIED LIFTING SLINGS (LIFTING LUGS ARE ONLY ADDED IF ORDERED AS AN OPTION - 6 LIFTING LUGS REQUIRED AS OPTION)
4	12" WIDE X 12" TALL FTS-MANUFACTURED PREFABRICATED CONCRETE DEADMAN (1,800 LBS EA) + HOLD-DOWN STRAPS AND TURNBUCKLES
2	12" WIDE X 12" TALL FTS-MANUFACTURED PREFABRICATED CONCRETE DEADMAN (2,400 LBS EA) + HOLD-DOWN STRAPS AND TURNBUCKLES
6	FTS-SUPPLIED HOLD DOWN STRAP LOCATION
	QTY 1 1 3 1 1 2 4 2 6

	DOUBLE-WALL
Tiberglass Tank	8-FT DIAMETER
SOLUTIONS Petroleum Storage Tanks	15,000-GALLON TANK
www.fgtsolutions.com	UL1316 - LISTED FUEL TANK
TANK WEIGHT DRY-MONITORED	7,400 LBS
TANK WEIGHT BRINE-MONITORED	8,300 LBS
ACTUAL CAPACITY 15,130 GALLONS	DRAWING NUMBER: FTSP- 250-005 DATE: 10/24/25